

## Instructions for Using WaterWicks

1. Make sure the diameter of your tank opening is big enough to insert and remove the WaterWick without resistance.
2. Extinguish cigarettes or any other burning materials before opening the fuel tank.
3. Hold the retrieval cord and slowly lower the WaterWick into the tank. Allow several minutes for the WaterWick to sink.
4. Be sure the retrieval cord length will allow the WaterWick to lie flat on the tank bottom. (This is where the water will be.) Shorten the retrieval cord to remove excess slack.
5. Attach the retrieval cord to the underside of the fuel cap or any location that still allows the cap to be replaced.
6. When the WaterWick is fully saturated, remove it from the fuel tank. Saturation will be indicated when the nylon inner bladder expands tightly against the outer casing. Saturation level should be checked monthly and replaced every three months regardless of saturation.
7. Install the WaterWick so that it will not obstruct the fuel outlet or sending unit. **THIS IS ESPECIALLY IMPORTANT IN MOVING VEHICLES.**



**NOTICE:** Alcohol-based fuel additives designed to disperse water reduce the effectiveness of the WaterWick.

**DISPOSAL NOTICE:** Used absorbents can be considered hazardous and must be disposed of in compliance with local, state and federal regulations.

**CAUTION:** Not to be used with on-road passenger vehicles, tanks with anti-siphon mechanisms or tanks with fill necks.